

A special oil for the Mercruiser base.

## PERFORMANCES

**Standards:**

API GL-5

## ADVANTAGES

Thanks to its extreme pressure additives, MARINE GEAR MC HP possesses a higher filling capacity.

MARINE GEAR MC HP offers excellent corrosion protection, and can be used under the most extreme temperature conditions.

## PHYSICO-CHEMICAL PROPERTIES

Characteristics	Methods	Units	Values
Colour	-	-	Blue
Viscosity grade	-	SAE	90
Viscosity at 100°C	ASTM D7042	mm <sup>2</sup> /s	15.2
Viscosity at 40°C	ASTM D7042	mm <sup>2</sup> /s	145.6
Flash point	ASTM D92	°C	193
Pour point	ASTM D97 B	°C	-23
Density at 20°C	ASTM D4052	g/Cm3	0.890

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: V-08-L-1507  
Published: 22/07/2024

