

Metalworking fluid.

DESCRIPTION & APPLICATIONS

- Drilling
- Tapping

Drilling/tapping fluid specially developed for hard materials (alloy steel and stainless steel). Particularly suited to very difficult work in refractory steel.

Its viscosity is designed to facilitate large diameter and deep tapping operations. This specific viscosity, combined with the extreme pressure, adhesion and lubricity properties of the fluid enable improved surface conditions and longer tool life to be achieved.

ADVANTAGES

- Extreme-pressure
- Adhesion
- Lubricity
- Long tool life

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Red fluid
Density at 15°C	NFT 60-101	kg/m ³	1059
Kinematic viscosity at 40°C	NFT 60-100	mm ² /s	150.2

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference: XI-100-1601
Date of issue: 11/01/2016