



## PRO 400X 15W-40

Ultra High Performance Diesel (UHPD) engine lubricant for severe use.

#### **PERFORMANCES**

#### Standards:

ACEA E7 / E11 / E9-16 API CK-4 / CJ-4 / CI-4 **API SN** JASO DH-2

## Spécifications :

MTU Type 2.1 **CATERPILLAR ECF-3** JCB 4001/2900 **DEUTZ DQC III-18 LA** DAF motorisations Euro VI VOLVO VDS-4.5 MERCEDES MB 228.31 MAN M3575 / M3775 **CUMMINS CES 20086 RVI RLD-3** MACK EO-S 4.5 JCB 4001/2900 **ALLISON TES 439** FORD WSS-M2C171-F1

#### **ADVANTAGES**

IGOL PRO 400X complies with the most stringent standards in force and is designed for use in applications such as public works, transport and agriculture.

IGOL PRO 400X is suitable for diesel engines with or without EGR, with or without particulate filter, and also for engines (anti-pollution standards: Euro VI - Tier 5 - Stage V) equipped with an exhaust gas after-treatment system with the SCR (selective catalytic reduction) process using Ad-Blue.

Its advantageous and versatile design has been developed for the latest generation of engines but is fully backwards compatible with earlier engines.

- Low Ash formulation for protection against particulate filter clogging.
- Optimizes engine cleanliness.
- Reduces deposit formation on pistons.
- Suitable for many applications due to these API and ACEA standards.





# PRO 400X 15W-40

### **PHYSICO-CHEMICAL PROPERTIES**

Characteristics	Standards	Units	Values
Density at 20°C	ASTM D4052	g/cm3	0.862
Viscosity at 40°C	ASTM D7042	mm²/s	95.4
Viscosity at 100°C	ASTM D7042	mm²/s	14.9
HTHS viscosity	ASTM D4683	mPa s	3.94
Viscosity index	ASTM D2270	-	164
Pour point	ASTM D97 B	°C	-42
COC flash point	ASTM D92	°C	232
TBN (Alkalinity reserve)	ASTM D2896	Mg KOH/g	10.7

**IGOL PRO 400X** is miscible with most conventional oils but to ensure its performance level it is recommended that a complete oil change be carried out.

#### Note: Before use, always check the manufacturer's recommendations

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : III-IGOL024 Date of issue : 21/02/2023

