

Mineral oil.

Multigrade lubricant for 4-stroke engines and particularly suitable for cars and light commercial vehicles.

PERFORMANCES

Standards: ACEA A3-98 / B3-98
API SJ/CF

ADVANTAGES

PROCESS GS is characterised by good anti-oxidant, anti-rust and anti-wear properties and thus contributes to an effective protection of your engine.

Suitable for all types of petrol and diesel engines with or without turbo, using all types of leaded or unleaded fuels, diesel and LPG, with or without catalytic converter.

PHYSICO-CHEMICAL PROPERTIES

Characteristics	Standards	Units	15W-40	20W-50
Density at 15°C	ASTM D4052	g/cm ³	0.865	0.869
Kinematic viscosity at 40°C	ASTM D7042	mm ² /s	93.7	124.3
Kinematic viscosity at 100°C	ASTM D7042	mm ² /s	13.8	17.1
Viscosity index	ASTM D2270	-	151	150
CCS @ -20°C	ASTM D5293	mPa.s	3312	-
CCS @ -15°C	ASTM D5293	mPa.s	-	2491
Pour point	ASTM D97	°C	-45	-42
VO flash point	ASTM D92	°C	221	221

Note: Before use, always check the manufacturer's recommendations

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref.: I-IGOL025-2111
Date of publication: 02/12/2021

Technical data sheet

