

PROFIL SUPER 2T

A semi-synthetic lubricant for 2-stroke engines.

PERFORMANCES

Standards:

API TC for 4% dose API TB for 3% dose API TB for 2% dose

ADVANTAGES

PROFIL SUPER 2T comprises synthetic agents and selected additives, in order to augment its very good anti-scaling properties.

Hence its specific additives keep engines remarkably clean, and in particular, prevent spark plug fouling.

The formulation of PROFIL SUPER 2T was developed to enable use of new fuels and to reduce smoke emissions.

PROFIL SUPER 2T is pre-diluted to facilitate its dispersal in the fuel.

For separate greasing or mixed with petrol.

USES

PROFIL SUPER 2T is a semi-synthetic lubricant for 2-stroke petrol engines. PROFIL SUPER 2T was developed for "leisure" use in 2 to 4% mixture with the fuel. Also suitable for any air-cooled 2-stroke engines (chainsaws, lawnmowers, etc.). PROFIL SUPER 2T is suitable for unleaded petrol (4% min.).

In mixture, the dose is 2 % to 4% (according to manufacturer's recommendations)

Carburant	Dosage à 2% (50:1)	Dosage à 3% (33:1)	Dosage à 4% (25:1)
1 Litre	20 ml	30 ml	40 ml
2 Litres	40ml	60 ml	80 ml
5 Litres	100 ml	150 ml	200 ml
10 Litres	200 ml	300 ml	400 ml



IGOL France - 614, rue de Cagny - CS 19403 - 80094 Amiens CEDEX 3 - FRANCE - T. +33 (0)3 22 47 79 47 - F. +33 (0)3 22 46 79 61 - www.igol.com



PROFIL SUPER 2T

PHYSICO-CHEMICAL CHARACTERISTICS

Characteristics	Methods	Units	Values
Colour	Visuel	-	Red
Density at 15°C	NF T 60-101	Kg/m3	890
Kinematic viscosity at 40°C	NF T 60-100	Mm²/s	76
Kinematic viscosity at 100°C	NF T 60-100	Mm²/s	9.9
Viscosity index	NF T 60-136	-	110
COC flash point	NF T 60-118	°C	120
Pour point	NF T 60-105	°C	-18

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref : I-IGOL018-2101 Published : 22/07/2024



IGOL France - 614, rue de Cagny - CS 19403 - 80094 Amiens CEDEX 3 - FRANCE - T. +33 (0)3 22 47 79 47 - F. +33 (0)3 22 46 79 61 - www.igol.com